

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

DARK

PRODUCT CODE
ŠIFRA PROIZVODA

JD32120



TEHNIČKI PODACI

Jednoručna baterija

Zidna montaža

Klasa protoka Z - 7 lit/min

NEOPERL® PERLATOR® COIN SLOT® - PPM24CSZ

Keramički mešač KEROX® 35 HWS - PKM35A

Heavy Duty ekscentar kolena - PEX42

Pokretni izliv 200mm - PIS200PIB

TECHNICAL DETAILS

Single lever mixer

Wall mounted

Flow class Z - 7 lit/min

NEOPERL® PERLATOR® COIN SLOT®

Ceramic cartridge KEROX® 35 HWS

Heavy Duty eccentric connectors

Swivel spout 200mm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

