

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

KING+

PRODUCT CODE
ŠIFRA PROIZVODA

JK371251



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Keramički mešač KEROX® 40 HWS
Podesivi usponski tuš
Ručni prebacivač
Zglobna tuš ruža D. 200mm
Duplo pleteno tuš crevo 1.5m
Easy Clean tuš ručica
Heavy Duty ekscentar kolena
Hromirane rozete

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Wall mounted
Ceramic cartridge KEROX®40 HWS
Adjustable height stand pipe shower
Manual diverter
Shower head D. 200mm
Double lock shower hose 1.5m
Easy Clean hand shower
Heavy Duty eccentric connectors
Chromed rossete

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

