

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

PERLA

PRODUCT CODE
ŠIFRA PROIZVODA

JP371001



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Regulacija protoka do 5 lit/min na tušu
Keramički mešač KEROX® 35 HWS
Duplo pleteno tuš crevo 1.5m
Ručni tuš
Heavy Duty ekscentar kolena
Hromirane rozete

TECHNICAL DETAILS

Single lever mixer
Wall mounted
Flow regulation on shower up to 5 lit/min
Ceramic cartridge KEROX® 35 HWS
Double lock shower hose 1.5m
Hand shower
Heavy Duty eccentric connectors
Chromed rossete

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

