

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

KLASIK

PRODUCT CODE
ŠIFRA PROIZVODA

K09201



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Otvorena veza bojler-baterija
Smanjeni protok 3 - 5 lit/min
Usmerivač NEOPERL® NEOSTRAHL®
Kompresioni gornji deo sa masnom komorom 1/2"
Metalni trokraki rukohvat
Hromirana rozeta
Pokretni izliv 200mm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Open flow waterheater-mixer
Reduced flow rate 3 - 5 lit/min
NEOPERL® NEOSTRAHL® Flow Straightener
Compression cartridge with grease chamber 1/2"
Metal triangle handle
Chromed rossette
Swivel spout 200mm

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

