

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

KLASIK

PRODUCT CODE
ŠIFRA PROIZVODA

K26102



TEHNIČKI PODACI

Dvoručna baterija
Montiranje na jedan otvor
Otvorena veza bojler-baterija
Smanjeni protok 3 - 5 lit/min
Usmerivač NEOPERL® NEOSTRAHL®
Kompresioni gornji deo sa masnom komorom 1/2"
Metalni trokraki rukohvat
Pokretni izliv 130mm
INOX set za pričvršćenje
IMQ sertifikovana fleksibilna priključna creva

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Single hole mounted
Open flow waterheater-mixer
Reduced flow rate 3 - 5 lit/min
NEOPERL® NEOSTRAHL® flow straightener
Compression cartridge with grease chamber 1/2"
Metal triangle handle
Swivel spout 130mm
Stainless Steel rapid instalation set
IMQ certified flexible connection hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

