

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# KLASIK fummé

PRODUCT CODE  
ŠIFRA PROIZVODA

**KF12101**



### TEHNIČKI PODACI

Dvoručna baterija  
Zidna montaža  
Regulacija protoka do 5 lit/min na tušu  
Kompresioni gornji deo sa masnom komorom 1/2"  
Rukohvat dim boje  
Duplo pleteno tuš crevo 1.5m  
Ručni tuš  
Ručni prebacivač  
Heavy Duty ekscentar kolena  
Hromirane rozete

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Two handle mixer  
Wall mounted  
Flow regulation on shower up to 5 lit/min  
Compression cartridge with grease chamber 1/2"  
Fumme handle  
Double lock shower hose 1.5m  
Hand shower  
Manual diverter  
Heavy Duty eccentric connectors  
Chromed rossettes

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

