

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BRONTEE

PRODUCT CODE
ŠIFRA PROIZVODA

NB12251



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Flühs® LIFETIME keramički gornji delovi
Metalni rukohvat
Podesivi usponski tuš
Specijalna Brontee završna obrad
Zglobna tuš ruža metalna D. 200mm
Duplo pleteno tuš crevo 1.5m
Metalna tuš ručica
Heavy Duty ekscentar kolena
Ručni prebacivač

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Flühs® LIFETIME ceramic head parts
Metal handle
Adjustable height stand pipe shower
Special Brontee finish
Metal Shower head D. 200mm
Double lock shower hose 1.5m
Solid brass hand shower
Heavy Duty eccentric connectors
Manual diverter

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

