

# SPECIFICATION SHEET

## TEHNIČKI LIST

---



COLLECTION  
SERIJA

# BRONTEE

PRODUCT CODE  
ŠIFRA PROIZVODA

**NB21101**



### TEHNIČKI PODACI

Dvoručna baterija  
Montiranje na jedan otvor  
Klasa protoka Z - 7 lit/min  
NEOPERL® PERLATOR® HONEYCOMB  
Flühs® LIFETIME keramički gornji delovi  
Specijalna Brontee završna obrad  
Metalni rukohvat  
Fiksni izliv  
INOX set za pričvršćenje  
IMQ sertifikovana fleksibilna priključna creva

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Two handle mixer  
Single hole mounted  
Flow class Z - 7 lit/min  
Aerator NEOPERL® PERLATOR® HONEYCOMB  
Flühs® LIFETIME ceramic head parts  
Special Brontee finish  
Metal handle  
Fixed spout  
Stainless Steel rapid instalation set  
IMQ certified flexible connection hoses

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

