

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

XO

PRODUCT CODE
ŠIFRA PROIZVODA

XO32115



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
Flühs® LIFETIME keramički gornji delovi
Heavy Duty ekscentar kolena
Hromirane minimalističke rozete
Pokretni izliv L. 150mm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Flow rate Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
Flühs® LIFETIME ceramic head parts
Heavy Duty eccentric connectors
Chromed minimalistic rossetes
Swivel spout L. 150mm

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

