

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

XO

PRODUCT CODE
ŠIFRA PROIZVODA

XO37251



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Regulacija protoka do 5 lit/min na tušu
Flühs® LIFETIME keramički gornji delovi
Podesivi usponski tuš
Ručni prebacivač
Zglobna tuš ruža D. 200mm
Duplo pleteno tuš crevo 1.5m
Easy Clean tuš ručica
Heavy Duty ekscentar kolena
Hromirane minimalističke rozete

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Flow regulation on shower up to 5 lit/min
Flühs® LIFETIME ceramic head parts
Adjustable height stand pipe shower
Manual diverter
Shower head D. 200mm
Double lock shower hose 1.5m
Easy Clean hand shower
Heavy Duty eccentric connectors
Chromed minimalistic rossete

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

