

Technical Datasheet

SM-23

Special nitro solvent

Description

SM-23 is a specially formulated solvent blend of aliphatic hydrocarbons, esters and ketones.

Fields of application

Specifically designed for thinning solvent-based enamel paints and cleaning application tools. Suitable also for pre-paint degreasing of metal surfaces.

Technical data

Color: clear / colorless

Density: 0.82 ± 0.02 kg/l

Directions for use

Before using SM-23, check the recommended thinning ratio of the product to be used. Then, add the required amount of SM-23 and stir until you get a homogeneous consistency.

Consumption

Consumption varies depending on the nature of the application.

Packaging

0.75 l & 4 l containers.

Shelf life – Storage

36 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

Remarks

- Ensure adequate ventilation when applying SM-23 indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the directions for safe use and precautions written on the packaging before use.
- For further information, please refer to the Material Safety Data Sheet.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 576 029

www.isomat.eu e-mail: support@isomat.eu