REVERSIBLE TORQUE WRENCHES

CERTIFIED PREMIUM INDUSTRIAL TOOLS

From 1/4" to 1"

1. The **ratchet gear is made in Cr-V** for maximum strength.
2. Wider range with **larger clamping range**, reaching from 2,5Nm to 3000N.
3. Increased number of **teeth** on the gear **45**, instead of 32, in order to **reduce the required minimum angle of rotation** from **11 º to 8 º**.
4. **Double scale window**, larger and more visible for having **torque adjustment more precise and accurate**. The scale in units Nm, lb.ft and Lb.in to square drive 1/4 ".
5. **Ergonomic non slip** BIMAT handle.
6. Push type **locking system**.
7. **Reversible** torque wrench with a gear lever.
8. **Mirror polished chrome plating**.
9. Individual carrying **case**.

12M 12 MONTHS OF WARRANTY / ALL MEASURING INSTRUMENTS MUST BE RE-CALIBRATED AFTER ONE YEAR OF BEING USED OR AFTER 10,000 CYCLES

REVERSIBLE TORQUE WRENCH



COD.	AF inch	N.m	Lb.ft	Lb.in	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Kg	
62951	1/4	2.5-12	-	20-105	290	28	30	19	38	0,8	1
62952		4-20		30-180							
65871		-		35-180	230						
62965	3/8	6-30		50-250	320	37	40	25		0,9	
65872		-		120-450	380	40	44			1,3	
62953		25-125	20-90	-	440	38	40				
57686	1/2	10-70	-	100-600			41			0,9	
62954		25-125	20-90	-			44			1,3	
65873		-	-	350-1800	520	40				1,4	
62963		40-200	30-150	-	460						
62968		65-335	50-250		520					1,5	
65918		-	-	1000-3000							
62983		80-400	60-300	-	750					1,9	
62969	3/4	160-800	120-600		1040	60	66	39		8,6	
62976	1	200-1000	150-750			72	82				
62977		300-1500	200-1100		1250			40		12	
62978		400-2000	300-1500							12,2	
62979		600-3000	400-2200							13,2	

12M | Repair kit available

TECHNICAL SPECIFICATION	
Accuracy	3%
Calibration certificate	●
Reversible	●
Teeth	45
Individual case	●

TECHNICAL SPECIFICATION		
MATERIAL	Body	Steel
	Handle	TPR (Black and red)
HARDNESS	Square drive	39 HRc.

EXTENSION BAR FOR TORQUE WRENCH

COD.	L (mm)	O.D. mm	Valid for	Kg	
56497	1100	38	62977, 62978, 56494, 56495	3,4	1
56498		40,5	62979, 56496	4,7	

12M 12 MONTHS OF WARRANTY / ALL MEASURING INSTRUMENTS MUST BE RE-CALIBRATED AFTER ONE YEAR OF BEING USED OR AFTER 10,000 CYCLES

This document has been created by and is the property of EGA Master S.L. Thus, all intellectual rights belong to EGA Master. Any total or partial copy of this document in any physical, electronic or any other form is strictly forbidden. EGA Master will legally proceed against any infringement of these rights.