

REVERSIBLE TORQUE WRENCHES

**From
1/4" to 1"**



1. The ratchet gear is made in Cr-V for maximum strength.

2. Wider range with larger clamping range, reaching from 2,5Nm to 3000N.

3. Increased number of teeth on the gear 45, instead of 32, in order to reduce the required minimum angle of rotation from 11 ° to 8 °.

4. Double scale window, larger and more visible for having torque adjustment more precise and accurate. The scale in units Nm, lb.ft and Lb.in to square drive 1/4 ".

5. Ergonomic non slip **BMAT** handle.


6. Push type locking system.

7. Reversible torque wrench with a gear lever.

8. Mirror polished chrome plating.

9. Individual carrying case.

REVERSIBLE TORQUE WRENCH



COD.		N.m	Lb.ft	Lb.in	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)		
62951	1/4	2.5-12		20-105	290	28	30	19		0,8	
62952		4-20		30-180							
65871		-	-	35-180	230						
62965	3/8	6-30		50-250	320	37	40			0,9	
65872		-		120-450	380	40	44			1,3	
62953		25-125	20-90	-			40				
57686	1/2	10-70	-	100-600	440	38	41			0,9	
62954		25-125	20-90	-				25		1,3	
65873		-	-	350-1800	520				38	1,4	1
62963		40-200	30-150	-	460		44				
62968		65-335	50-250			40					
65918		-	-	1000-3000	520					1,5	
62983	3/4	80-400	60-300		750					1,9	
62969		160-800	120-600		1040	60	66	39		8,6	
62976		200-1000	150-750	-							
62977	1	300-1500	200-1100			72	82			12	
62978		400-2000	300-1500		1250			40		12,2	
62979		600-3000	400-2200							13,2	



12M | Repair kit available

TECHNICAL SPECIFICATION	
Accuracy	3%
Calibration certificate	●
Reversible	●
Teeth	45
Individual case	●

TECHNICAL SPECIFICATION	
MATERIAL	Body: Steel
	Handle: TPR (Black and red)
HARDNESS	Square drive: 39 HRC.

EXTENSION BAR FOR TORQUE WRENCH

COD.	L (mm)	Ø D. mm	Valid for	Kg	
56497	1100	38	62977, 62978, 56494, 56495	3,4	1
56498		40,5	62979, 56496	4,7	

