

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ

PRODUCT CODE
ŠIFRA PROIZVODA

131401



TEHNIČKI PODACI

Jednoručna baterija
Uzidna montaža
Masivna konstrukcija
Keramički mešač KEROX® 35 HWS
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® COIN SLOT®

TECHNICAL DETAILS

Single lever mixer
Built-in the wall
Solid construction
Ceramic cartridge KEROX® 35 HWS
Flow class Z - 7 lit/min
Aerator NEOPERL® PERLATOR® COIN SLOT®

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

131401B



TEHNIČKI PODACI

Jednoručna baterija
Uzidna montaža
Masivna konstrukcija
Keramički mešač KEROX® 35 HWS
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® COIN SLOT®

TECHNICAL DETAILS

Single lever mixer
Built-in the wall
Solid construction
Ceramic cartridge KEROX® 35 HWS
Flow class Z - 7 lit/min
Aerator NEOPERL® PERLATOR® COIN SLOT®

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

