

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ

PRODUCT CODE
ŠIFRA PROIZVODA

133101



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka C
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® Hybrid
HD ekscentar kolena 48mm sa utišivačem
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Solid construction
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® Hybrid
HD 48mm eccentric connectors with silencer
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

133101B



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka C
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® Hybrid
HD ekscentar kolena 48mm sa utišivačem
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Solid construction
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® Hybrid
HD 48mm eccentric connectors with silencer
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ WHITE

PRODUCT CODE
ŠIFRA PROIZVODA

133101W



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka C
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® Hybrid
HD ekscentar kolena 48mm sa utišivačem
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Solid construction
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® Hybrid
HD 48mm eccentric connectors with silencer
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

