

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ

PRODUCT CODE
ŠIFRA PROIZVODA

137351



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka 9lit/min
Tuš ruža D.220mm sa zglobom
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® CDV-18
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm
HD ekscentar kolena 48mm sa utišivačem

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Flow rate 9 lit/min
Shower rose D.220mm with knob
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® CDV-18
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm
HD 48mm eccentric connectors with silencer

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

137351B



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka 9lit/min
Tuš ruža D.220mm sa zglobom
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® CDV-18
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm
HD ekscentar kolena 48mm sa utišivačem

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Flow rate 9 lit/min
Shower rose D.220mm with knob
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® CDV-18
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm
HD 48mm eccentric connectors with silencer

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ WHITE

PRODUCT CODE
ŠIFRA PROIZVODA

137351W



TEHNIČKI PODACI

Jednoručna baterija
Montaža na zid
Klasa protoka 9lit/min
Tuš ruža D.220mm sa zglobom
Keramički mešač KEROX® 35 OP HWS
Automatski prebacivač NEOPERL® CDV-18
Easy Clean STOLZ tuš ručica
STOLZ duplo pleteno tuš crevo 150cm
HD ekscentar kolena 48mm sa utišivačem

TECHNICAL DETAILS

Single lever mixer
Wall assembly
Flow rate 9 lit/min
Shower rose D.220mm with knob
Ceramic cartridge KEROX® 35 OP HWS
Automatic diverter NEOPERL® CDV-18
Easy Clean STOLZ hand shower
STOLZ double locked shower hose 150cm
HD 48mm eccentric connectors with silencer

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

