

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2

PRODUCT CODE  
ŠIFRA PROIZVODA

## 230101



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Hromirana završna obrada  
Montiranje na jedan otvor  
Klasa protoka Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Keramički mešač CITEC® 25mm - PKM25SA  
Set za pričvršćenje sa jednim vijkom  
NEOPERL® SPX® priključna creva - FB50PX

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Chrome finish  
Single hole assembly  
Flow rate Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
CITEC®25 mm ceramic cartridge - PKM25SA  
Single screw fixing set  
NEOPERL® SPX® connecting hoses - FB50PX

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)



# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2 BLACK

PRODUCT CODE  
ŠIFRA PROIZVODA

**230101B**



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - Matt black  
Montiranje na jedan otvor  
Klasa protoka Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Keramički mešač CITEC® 25mm - PKM25SA  
Set za pričvršćenje sa jednim vijkom  
NEOPERL® SPX® priključna creva - FB50PX

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Matt black finish  
Single hole assembly  
Flow rate Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
CITEC®25 mm ceramic cartridge - PKM25SA  
Single screw fixing set  
NEOPERL® SPX® connecting hoses - FB50PX

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)



# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2 GOLD

PRODUCT CODE  
ŠIFRA PROIZVODA

**230101G**



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - PVD brušeno zlato  
Montiranje na jedan otvor  
Klasa protoka Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Keramički mešač CITEC® 25mm - PKM25SA  
Set za pričvršćenje sa jednim vijkom  
NEOPERL® SPX® priključna creva - FB50PX

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Brushed gold PVD finish  
Single hole assembly  
Flow rate Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
CITEC®25 mm ceramic cartridge - PKM25SA  
Single screw fixing set  
NEOPERL® SPX® connecting hoses - FB50PX

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

