

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

231901



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Uzidna baterija
Automatski prebacivač za tuš
Keramički mešač KEROX® 35mm - PKM35A

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Build in the wall
Automatic shower diverter
KEROX®35 mm ceramic cartridge - PKM35A

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

231901B



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - Matt black
Uzidna baterija
Automatski prebacivač za tuš
Keramički mešač KEROX® 35mm - PKM35A

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Matt black finish
Build in the wall
Automatic shower diverter
KEROX®35 mm ceramic cartridge - PKM35A

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 GOLD

PRODUCT CODE
ŠIFRA PROIZVODA

231901G



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD brušeno zlato
Uzidna baterija
Automatski prebacivač za tuš

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Brushed gold PVD finish
Build in the wall
Automatic shower diverter

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C