

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

Thermo S2

PRODUCT CODE
ŠIFRA PROIZVODA

2T31901



TEHNIČKI PODACI

Termostatska baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Uzidna baterija
Termostatski uložak PKMTS2

TECHNICAL DETAILS

Thermo regulation mixer
Minimalist design
Solid brass body
Chrome finish
Build in the wall
Thermostatic cartridge PKMTS2

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

Thermo S2

PRODUCT CODE
ŠIFRA PROIZVODA

2T31901B



TEHNIČKI PODACI

Termostatska baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD Dark black
Uzidna baterija
Termostatski uložak PKMTS2

TECHNICAL DETAILS

Thermo regulation mixer
Minimalist design
Solid brass body
Dark black PVD finish
Build in the wall
Thermostatic cartridge PKMTS2

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C