

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

330101



TEHNIČKI PODACI

Jednoručna baterija
Moderan dizajn
Telo od mesinga
Hromirana završna obrada
Fiksiranje na jedan otvor
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
Keramički mešač Hydroplast 25mm GX25
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključna creva - FB50PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Modern design
Solid brass body
Chrome finish
Single hole assembly
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
Hydroplast 25 mm ceramic cartridge GX25
Single screw fixing set
NEOPERL® SPX® connecting hoses - FB50PX

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

330101B



TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Matt Black završna obrada

Fiksiranje na jedan otvor

NEOPERL® SLIMAIR® SLC® SSR® - PPM24SA

Keramički mešač Hydroplast 25mm GX25

Set za pričvršćenje sa jednim vijkom

NEOPERL® SPX® priključna creva - FB50PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Matt Black finish

Single hole assembly

NEOPERL® SLIMAIR® SLC® SSR® - PPM24SA

Hydroplast 25 mm ceramic cartridge GX25

Single screw fixing set

NEOPERL® SPX® connecting hoses - FB50PX

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN