

# SPECIFICATION SHEET

## TEHNIČKI LIST



# STOLZ

COLLECTION  
SERIJA

# S3

PRODUCT CODE  
ŠIFRA PROIZVODA

# 338101



### TEHNIČKI PODACI

Jednoručna baterija  
Moderan dizajn  
Telo od mesinga  
Hromirana završna obrada  
Fiksiranje na jedan otvor  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Keramički mešač Hydroplast 25mm GX25  
Set za pričvršćenje sa jednim vijkom  
NEOPERL® SPX® priključna creva - FB50PX  
Pokretni izliv

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Modern design  
Solid brass body  
Chrome finish  
Single hole assembly  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Hydroplast 25 mm ceramic cartridge GX25  
Single screw fixing set  
NEOPERL® SPX® connecting hoses - FB50PX  
Swivel spout

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

# SPECIFICATION SHEET

## TEHNIČKI LIST

# STOLZ

COLLECTION  
SERIJA

# S3

PRODUCT CODE  
ŠIFRA PROIZVODA

# 338101B



### TEHNIČKI PODACI

Jednoručna baterija  
Moderan dizajn  
Telo od mesinga  
Hromirana završna obrada  
Fiksiranje na jedan otvor  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Keramički mešač Hydroplast 25mm GX25  
Set za pričvršćenje sa jednim vijkom  
NEOPERL® SPX® priključna creva - FB50PX  
Pokretni izliv

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Modern design  
Solid brass body  
Chrome finish  
Single hole assembly  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Hydroplast 25 mm ceramic cartridge GX25  
Single screw fixing set  
NEOPERL® SPX® connecting hoses - FB50PX  
Swivel spout

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C