

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

339101



TEHNIČKI PODACI

Jednoručna baterija
Moderan dizajn
Telo od mesinga
Hromirana završna obrada
Fiksiranje na jedan otvor
NEOPERL® HONEYCOMB®- PPM22N
Keramički mešač Hydroplast 25mm GX25
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključna creva - FB50PX
Pokretni izliv

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Modern design
Solid brass body
Chrome finish
Single hole assembly
NEOPERL® HONEYCOMB®- PPM22N
Hydroplast 25 mm ceramic cartridge GX25
Single screw fixing set
NEOPERL® SPX® connecting hoses - FB50PX
Swivel spout

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

339101B



TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Hromirana završna obrada

Fiksiranje na jedan otvor

NEOPERL® HONEYCOMB® - PPM2224U

Keramički mešač Hydroplast 25mm GX25

Set za pričvršćenje sa jednim vijkom

NEOPERL® SPX® priključna creva - FB50PX

Pokretni izliv

TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Chrome finish

Single hole assembly

NEOPERL® HONEYCOMB® - PPM2224U

Hydroplast 25 mm ceramic cartridge GX25

Single screw fixing set

NEOPERL® SPX® connecting hoses - FB50PX

Swivel spout

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN