

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S4

PRODUCT CODE
ŠIFRA PROIZVODA

431401



TEHNIČKI PODACI

Jednoručna baterija
Moderan dizajn
Telo od mesinga
Hromirana završna obrada
Ugradnja u zid
NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS
Keramički mešač KEROX 35mm Progressiv PKM35APR

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Modern design
Solid brass body
Chrome finish
Build-in wall solution
NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS
KEROX 35 mm ceramic cartridge progressiv PKM35APR

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S4

PRODUCT CODE
ŠIFRA PROIZVODA

431401B



TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Matt Black završna obrada

Ugradnja u zid

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

Keramički mešač KEROX 35mm Progressiv PKM35APR

TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Matt Black finish

Build-in wall solution

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

KEROX 35 mm ceramic cartridge progressiv PKM35APR

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN