

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BLAU

PRODUCT CODE
ŠIFRA PROIZVODA

B133530



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Klasa protoka C - na izlivu
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač Blau OP-A
Polu-Automatski prebacivač za tuš
INOX 304 ekscentar kolena
Konusne hromirane rozete
Zglobna tuš ruža D. 220mm PTRUSP70
Duplo pleteno tuš crevo 1.5m
Tuš ručica 3 Funkcije - PTR3C70
+ Baterija za lavabo B130100

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Wall mounted
Flow class C - on spout
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge Blau OP-A
Half-Automatic shower diverter
INOX 304 eccentric connectors
Chrome plated conical rosets
Shower head D. 220mm PTRUSP70
Double lock shower hose 1.5m
3 Function hand shower - PTR3C70
+ Basin mixer B130100

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BLAU

PRODUCT CODE
ŠIFRA PROIZVODA

B133530B



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Klasa protoka C - na izlivu
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač Blau OP-A
Polu-Automatski prebacivač za tuš
INOX 304 ekscentar kolena
Konusne crne rozete
Zglobna tuš ruža D. 220mm **PTRUSP70B**
Duplo pleteno tuš crevo 1.5m Black
Tuš ručica 3 Funkcije - **PTR3C70B**
+ Baterija za lavabo **B130100B**

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Wall mounted
Flow class C - on spout
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge Blau OP-A
Half-Automatic shower diverter
INOX 304 eccentric connectors
Matt black conical rosets
Shower head D. 220mm **PTRUSP70B**
Double lock shower hose 1.5m Black
3 Function hand shower - **PTR3C70B**
+ Basin mixer **B130100B**

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

