

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

QUADRO

PRODUCT CODE
ŠIFRA PROIZVODA

JQ30201



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
Keramički mešač KEROX® 35 OP HWS
INOX set za pričvršćenje
NEOPERL® SPX® priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow class Z - 7 lit/min
Aerator NEOPERL® PERLATOR® HONEYCOMB
Ceramic cartridge KEROX® 35 OP HWS
Stainless Steel rapid instalation set
NEOPERL® SPX® flexible hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

QUADRO BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

JQ30201B



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
Keramički mešač KEROX® 35 OP HWS
INOX set za pričvršćenje
NEOPERL® SPX® priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow class Z - 7 lit/min
Aerator NEOPERL® PERLATOR® HONEYCOMB
Ceramic cartridge KEROX® 35 OP HWS
Stainless Steel rapid instalation set
NEOPERL® SPX® flexible hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs



SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

QUADRO WHITE

PRODUCT CODE
ŠIFRA PROIZVODA

JQ30201W



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
Keramički mešač KEROX® 35 OP HWS
INOX set za pričvršćenje
NEOPERL® SPX® priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow class Z - 7 lit/min
Aerator NEOPERL® PERLATOR® HONEYCOMB
Ceramic cartridge KEROX® 35 OP HWS
Stainless Steel rapid instalation set
NEOPERL® SPX® flexible hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

