

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

XENON

PRODUCT CODE
ŠIFRA PROIZVODA

JX38701



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka S
Pokretni izliv 360°
FaST35 set za brzo pričvršćenje
NEOPERL® SPX® priključna creva

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow class S
Swivel spout 360°
FaST35 fixing set
NEOPERL® SPX® flexible connecting hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs
www.rosan.rs

ROSAN

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

XENON

PRODUCT CODE
ŠIFRA PROIZVODA

JX38701B



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka S
Pokretni izliv 360°
FaST35 set za brzo pričvršćenje
NEOPERL® SPX® priključna creva

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow class S
Swivel spout 360°
FaST35 fixing set
NEOPERL® SPX® flexible connecting hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs
www.rosan.rs

ROSAN